

POWERSCAN™ PD9300 AR LASER



INDUSTRIAL LASER BAR CODE READER

The PowerScan 9000 product series is Datalogic's premium line of rugged industrial handheld data collection products. The PowerScan PD9330 AR laser scanner offers state-of-the-art performance in a hand held corded industrial product with extra-long scanning capabilities.

SUPERIOR READING PERFORMANCE

The PD9330 reader features Datalogic's exclusive 3 Green Lights (3GL™) for superior good read feedback. The patented 'Green Spot' technology directly on the code and dual Good Read LEDs on the top of the cap increase visibility at any angle.

BUILT TO LAST

The PD9330 reader's mechanics have been developed and tested to withstand extreme environmental conditions, maintaining consistent reading performance without degrading performance or reliability. Its ergonomic enclosure is lightweight and well-balanced to ensure optimal operator comfort during scan-intensive operations. A built-in metal tether hook for suspended applications ensures workplace productivity.

DEVELOPED WITH THE USER IN MIND

All models have multi-interface capabilities built in featuring the most popular interfaces; RS-232, Keyboard Wedge and USB. The Datalogic Aladdin™ configuration program provides user-friendly features that simplify the start-up procedure, even for inexperienced users.

FEATURES

- Optics available in:
 - **Auto Range:** up to 11.5 m / 37.0 ft on reflective codes
- Datalogic's 3GL technology and a loud beeper for good-read feedback
- Built-in multiple interfaces (RS-232, Keyboard Wedge and USB)
- Operates over a wide range of temperatures
- Water and Particulate Sealing Rating: IP65
- Drop resistance to 2.0 m / 6.5 ft
- Ergonomic shape provides hours of tireless data collection for the user
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY - APPLICATION

- Manufacturing Shop Floor:
 - Work-in-Progress
 - Sub-Assembly
 - Component Tracking
 - Quality Control
 - Time and Cost Analysis
 - Machine Replenishment / Configuration
 - Line Inventory Control
- Warehouse and Logistic Centers:
 - Shipping / Receiving
 - Parcel Preparation
 - Picking / Put Away
 - Automatic Sorting Back-Up
 - End of Line Sorting



POWERSCAN™ PD9330 AR LASER

TECHNICAL SPECIFICATIONS

DECODING CAPABILITY	
PD9330-AR (Auto Range)	GS1 DataBar™ linear codes, UPC/EAN, UPC/EAN P2/ P5 add ons, UPC/EAN Coupons, ISBN, Code 128, EAN 128, Code 39, Code 39 Full ASCII, Code 32, Codabar, Interleaved 2 of 5, Standard 2 of 5, MSI, Code 93
ELECTRICAL	
Current	Operating (Max. reading): PD9330-AR: 480 mA @ 4.5 V; 420 mA @ 5V; 80 mA @ 30 V
Input Voltage	4.5 - 30 VDC
ENVIRONMENTAL	
Ambient Light	Immune to light exposure in offices/facilities and direct exposure to sunlight
Drop Resistance	Withstands 50 drops from 2.0 m / 6.5 ft to concrete
ESD Protection (Air Discharge)	20 kV
Humidity (Non-Condensing)	0 - 95%
Particulate and Water Sealing	IP65
Temperature	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F
INTERFACES	
Interfaces	Keyboard Wedge; RS-232; USB
PHYSICAL CHARACTERISTICS	
Colors Available	Yellow/Black; Other colors and custom logo options are available for minimum quantity purchase
Dimensions	21.2 x 11.0 x 7.4 cm / 8.4 x 4.3 x 2.9 in
Weight	PD9330-AR: 375 g / 13.2 oz
READING PERFORMANCE	
Light Source	630 - 680 nm VLD
Print Contrast Ratio (Minimum)	25%
Read Rate (Maximum)	Scan Rate: PD9330-AR: 35 +/- 5 scans/sec.
Reading Angle	PD9330-AR: Pitch: +/- 60°; Roll (Tilt): +/- 10°; Skew (Yaw): +/- 65°
Reading Indicators	Beeper; Datalogic Three Green Lights (3GL™) Good Read Feedback; Datalogic 'Green Spot' on the Code, Dual Good Read LEDs
Resolution (Maximum)	PD9330: Auto Range: 0.190 mm / 7.5 mils

READING RANGES	
Typical Depth of Field	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast and ambient light dependent.
PD9330 AR: Code 39	7.5 mils: 9.0 to 50.0 cm / 3.5 to 19.7 in
	10 mils: 14.0 to 85.0 cm / 5.5 to 33.5 in
	15 mils: 15.0 to 155.0 cm / 5.9 to 61.0 in
	20 mils: 15.0 to 220.0 cm / 5.9 to 86.6 in
	40 mils: 20.0 to 340.0 cm / 7.9 to 133.9 in
PD9330 AR: Code 39	55 mils: 25.0 to 420.0 cm / 9.8 to 165.4 in
	Reflective Labels: Code 39: 70 mils: up to 9.0 m / 29.0 ft
PD9330 AR: Code 39	100 mils: up to 11.5 m / 37 ft
	Note: Reading Performances may change with different symbologies
SAFETY & REGULATORY	
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use. See the Regulatory Addendum for details.
Environmental Compliance	Complies to China RoHS; Complies to EU RoHS
Laser Classification	Caution Laser Radiation - Do not stare into beam; CDRH Class II; IEC 60825-1 Class 2
UTILITIES	
Datalogic Aladdin™	Datalogic Aladdin configuration program is available for download at no charge.
OPOS / JavaPOS	OPOS and JavaPOS utilities are available for download at no charge.
Remote Host Download	Available on request
WARRANTY	
Warranty	3-Year Factory Warranty

ACCESSORIES

Cases / Holsters



HLS-P080 Universal Holster (HLS-8000)

Mounts / Stands



STD-P090 Stand, Hands-free (STD-9000)



HLD-P080 Desk/Wall Holder (HLD-8000)



7-0404 Industrial Take-Up Reel